

# C-SERIES OPTIONS



**The C-Series consists of quiet, energy-efficient and compact ovens with high flexibility, which are designed to fit into small spaces.**

The C-Series' compact ovens have room for one rack and are available in four sizes, which can all be powered by electricity, oil or gas. The oven's smart control panel and well-conceived design make it very user-friendly in most types of bakeries.



# C-SERIES OPTIONS

- 1. Rotating platform with adjustable ramp**  
The rotating platform makes it possible to use the majority of racks. Made of stainless steel. Maximum load 150 kg.
- 2. Heavy duty platform**  
Robust floor from selected materials to achieve the best lifespan. Maximum load 350 kg.
- 3. Automatic rack lifting device**  
The oven can be supplied with a motor driven hook that lifts the racks from the oven floor, making loading and unloading easier. This option means that the rack does not need to be lifted up onto a ramp or hook. The rack is placed on the floor, after which it is lifted and begins to rotate. Once baking is complete, the rack is automatically lowered to the floor of the oven so that it can be easily removed.
- 4. Large double glazed window in insulated door**  
Easier monitoring of the baking process but less energy efficient.
- 5. Insulated floor**  
Reduces heat leakage to the floor underneath. Height 35 mm.
- 6. Left hand hinged insulated door with double glazed window and door stop**  
The oven is supplied with a right-hand door as standard.
- 7. AES - Automatic Evacuation System**  
Evacuation system for a better working environment in the bakery. Hot air and steam is ventilated through a fan from the oven when the handle is turned upwards before opening the door.
- 8. Fully assembled oven**  
The oven is delivered fully assembled, reducing installation and start-up time.
- 9. Slow start**  
Smooth and gradually accelerating rotation of the rack for baking of products that are sensitive to motion and bumps, or which risk moving about due to vibrations.
- 10. Canopy**  
A large, solid canopy made of stainless steel. Effectively catches steam and unpleasant smells when the oven door is opened. Can be equipped with a fan for more efficient extraction.
- 11. Canopy with fan**  
A large, solid canopy made of stainless steel. Equipped with a fan for effective ventilation of steam and odors.
- 12. Variable speed for fans**  
The fan speed is driven by a frequency converter to maintain the desired flow of air. Helpful when baking sensitive products such as meringues, macaroons and muffins.

## Dimensions

**C100**  
Width: 1335 mm  
Height: 2292 mm  
Depth: 1353 mm  
Depth with canopy: 2208 mm

**C101 / C102**  
Width: 1335 mm  
Height: 2381 mm  
Depth: 1353 mm  
Depth with canopy: 2208 mm

**C150**  
Width: 1335 mm  
Height: 2523 mm  
Depth: 1353 mm  
Depth with canopy: 2208 mm

**C151 / C152**  
Width: 1335 mm  
Height: 2613mm  
Depth: 1353 mm  
Depth with canopy: 2208 mm

**C200**  
Width: 1450 mm  
Height: 2291 mm  
Depth: 1353 mm  
Total depth with canopy: 2208 mm

**C201 / C202**  
Width: 1450 mm  
Height: 2379 mm  
Depth: 1353 mm  
Total depth with canopy: 2208 mm

**C250**  
Width: 1450 mm  
Height: 2524 mm  
Depth: 1353 mm  
Total depth with canopy: 2208 mm

**C251 / C252**  
Width: 1450 mm  
Height: 2611 mm  
Depth: 1353 mm  
Total depth with canopy: 2208 mm

	C100	C101	C102	C150	C151	C152	C200	C201	C202	C250	C251	C252
Rotating platform with adjustable ramp	○	○	○	○	○	○	○	○	○	○	○	○
Heavy duty platform	○	○	○	○	○	○	○	○	○	○	○	○
Automatic rack lifting device	○	○	○	○	○	○	○	○	○	○	○	○
Large double glazed window in insulated door	○	○	○	○	○	○	○	○	○	○	○	○
Insulated floor	○	○	○	○	○	○	○	○	○	○	○	○
Left hand hinged door	○	○	○	○	○	○	○	○	○	○	○	○
AES - Automatic Evacutaion System	○	○	○	○	○	○	○	○	○	○	○	○
Fully assembled oven	○	○	○	○	○	○	○	○	○	○	○	○
Slow start	○	○	○	○	○	○	○	○	○	○	○	○
Canopy	○	○	○	○	○	○	○	○	○	○	○	○
Canopy with fan	○	○	○	○	○	○	○	○	○	○	○	○
Variable speed for fans	○	○	○	○	○	○	○	○	○	○	○	○
Sveba Connect	○	○	○	○	○	○	○	○	○	○	○	○
Water filter	○	○	○	○	○	○	○	○	○	○	○	○

● Standard  
○ Options

[www.sveba-dahlen.com](http://www.sveba-dahlen.com)