

# FERMATIC Q4

## TECHNICAL

MODEL WIDTH X DEPTH	RETARDER/ FREEZER DOUGH WEIGHT	NUMBER OF FANS	HEATING- EFFECT	COOLING EFFECT* RETARDER	COOLING EFFECT* FREEZER
<b>1000 x 1000</b>	30 kg	1	2 kW	1.0 kW	1.1 kW
<b>A 1000 x 1200</b>	30 kg	1	2 kW	1.0 kW	1.1 kW
<b>A 1000 x 1600</b>	60 kg	1	4 kW	1.8 kW	1.4 kW
<b>1000 x 2000</b>	90 kg	1	4 kW	2.0 kW	1.4 kW
<b>1600 x 1000</b>	60 kg	2	4 kW	1.8 kW	2.0 kW
<b>B 1600 x 1200</b>	60 kg	2	4 kW	1.8 kW	2.0 kW
<b>1600 x 1600</b>	120 kg	2	6 kW	3.1 kW	2.9 kW
<b>1800 x 1000</b>	90 kg	2	4 kW	2.5 kW	2.8 kW
<b>1800 x 1200</b>	90 kg	2	4 kW	2.5 kW	2.8 kW
<b>C 1800 x 1600</b>	180 kg	2	6 kW	4.3 kW	3.1 kW
<b>1800 x 2200</b>	180 kg	3	8 kW	4.4 kW	3.9 kW
<b>1800 x 2800</b>	360 kg	3	10 kW	5.5 kW	3.9 kW
<b>D 2000 x 1600</b>	180 kg	3	8 kW	4.4 kW	4.0 kW
<b>2000 x 2400</b>	270 kg	3	10 kW	5.8 kW	4.0 kW

Fermatic Q4 with a width of 1000 mm is equipped with one door.

Fermatic Q4 with widths of 1600, 1800 and 2000 mm are equipped with two doors.

\* Recommended effect

\*\* Insulated heated floor is standard on Freezer/Prover